

Evoke 5000B LED Bi-color Spot Light

Introducing the World's First 5000W LED Bi-Color Spot Light with **Green/Magenta** Adjustability



► Features

- **Innovative Nebula B4 light engine** to achieve 2700K-6500K with G/M±80 adjustment
- Light and shadow quality comparable to natural sunlight
- **IP66** rating for robust weather protection
- **Weighing only 43.119kg/95.06lb**, made of magnesium alloy for significant weight reduction
- **All-in-one design** integrates the lamp head, control unit, and adapter into one fixture
- **Refined usability features** like the balance adjusting rail, skid, and the new PosiTight tightening enhancement of the NL mount
- **Linear dimming** from 0.0% to 100.0%, with precise control between 0.0% and 0.1%
- **Multiple control methods**
On-board, Remote Controller, NANLINK APP, DMX/RDM, LumenRadio CRMX, Art-Net/sACN, Wired Controller
- **5 fan modes**
SMART, FULL SPEED, LOW SPEED, PAUSE, OFF
- **NL mount and complete accessory ecosystem**, compatible with most Evoke 2400B accessories and featuring versatile accessories specifically developed for the Evoke 5000B

► Target Market

- Motion picture lighting
- High-speed shooting

► What's in the Box

① **Standard Kit** Art.-Nr. 9449232

Evoke 5000B × 1
Yoke × 1
AC Cable 2m × 1 (for 200-240V countries/regions), or AC Cable 7.5m × 1 (for 100-125V countries/regions)
Reflector × 1
USB Flash Drive × 1
WC-EXT Wired Controller × 1 (Connection Cable 8m × 1, AS-MB-1 Magnetic Base × 1, Carrying Bag × 1)
User Manual × 2 (Evoke 5000B+WC-EXT)



② **Flight Case Kit** Art.-Nr. 9449227

Evoke 5000B × 1
Yoke × 1
AC Cable 2m × 1 (for 200-240V countries/regions), or AC Cable 7.5m × 1 (for 100-125V countries/regions)
Reflector × 1
USB Flash Drive × 1
CC-EV5000-FT Flight Case × 1
WC-EXT Wired Controller × 1 (Connection Cable 8m × 1, AS-MB-1 Magnetic Base × 1, Carrying Bag × 1)
User Manual × 2 (Evoke 5000B KIT+WC-EXT)



► *Specification*

Model	Evoke 5000B
Rated Power	200V-240V: 5000W 100V-125V: 5200W
Input Voltage/Current	AC100V-240V/52A(Max) 50/60Hz
Beam Angle	95°
CCT	2700K-6500K (G/M±80)
CRI	Average 97
TLCI	Average 98
TM-30 Rf	Average 96
TM-30 Rg	Average 102
SSI (3200K)	85
SSI (5600K)	74
Dimming	0.0%-100.0%, by 0.1% increment

KAISER[®]
FOTOTECHNIK

Kaiser Fototechnik GmbH & Co. KG
Im Krötenteich 2 · 74722 Buchen · Germany
Telefon +49(0)6281 407-0 · Fax +49(0)6281 407-55
www.kaiser-fototechnik.de · info@kaiser-fototechnik.de

► Accessories (Optional)

Picture				
Product	FL-45E Motorized Fresnel Lens 16°-50° NEW!	FL-35E Motorized Fresnel Lens 15°-46° *Max 50% output	RF-NL-PB NL70 Parallel Beam Reflector	RF-NLM-30/60-EV2400 30°/60° Reflector
Position on the balance adjusting rail	6	5	5	1
Picture				
Product	SB-NLM-100-S Square Softbox 100cm	LT-NLM-120 Lantern Softbox 120cm	SB-NLM-120-PR Parabolic Softbox 120cm	SB-NLM-150-PR Parabolic Softbox 150cm
Position on the balance adjusting rail	1	1	2	3
Picture				
Product	SB-NLM-150-O Octagonal Softbox 150cm	BD-NLM Barndoor for Evoke	PJ-NLM-15-30 Projection Attachment 15-30° *Max 50% output	AS-PJA-EV Projection Adapter *Max 50% output
Position on the balance adjusting rail	1	1	5	N/A
Picture	Coming soon			
Product	YK-E-EVL Evoke 5000B Motorized Yoke NEW!	CC-EV5000-FT Flight Case	WC-EXT Wired Controller *Included NEW! IP66	WC-LM6P-C1 6 Pin Wired Controller
Position on the balance adjusting rail	Coming soon	N/A	N/A	N/A