

SUMOSPACE

You asked for a bi-color fixture with the output of a 6K space light and the power consumption of an LED, for vibrant color rendition that needs no adjustment or filtering, for entirely passive cooling without fans, for interchangeable optics for incredible output and beam control, and for a light and durable construction under 5.5 Kg. With the SUMOSPACE we invite you to re-imagine with us the concept of studio overhead lighting.


SUMOLIGI




MADE IN GERMANY

TECHNICAL SPECIFICATIONS

- Powerful Output up to 13,500 Lux [1,254 fc] at 3 m [10 ft]
- Bi-Color, Smooth and Accurate Color Adjustment 3,000-6,000 K
- Ultra High Color Rendition TLCI 99, CRI 95
- Interchangeable Optics for 30°, 60°, 120° Beam Angle
- 0-100% Dimming Range
- Flicker Free at Infinite Frame Rates
- DMX/RDM, Ethernet and Wireless Interfaces
- Passive Cooled, No Fans or Moving Parts
- 500 W Power Consumption
- Fixture Weight 5.5 Kg [12 lbs]







SUMOSPACE

with Optics



With Reflector

With Reflector. Short Skirt and Target



With Reflector. Long Skirt and -Target



With Reflector, Long Skirt, Target and Half Black Skirt



Long Skirt, Target

and Black Skirt



SUMOSPACE on Yoke



SUMOLIGHT GMBH BERLIN TEL +49 30 2461 2753 INFO@SUMOLIGHT.COM MADE IN GERMANY I SUMOLIGHT.COM


and Target

SUMOLIGHT



SUMOSPACE CONFIGURATIONS

PHOTOMETRICS



Bi-Color Unit measured at 4,500 K

COLOR RENDITION