

Vantage Compatibility Chart

Go beyond a PTZ and future proof your studio

-							nots
		cu ^s	11/6/	11/61			edwithSi
	ć	metor	on recar in nec	at with VR	a col	be	save cessin
tures	lens 200	ons posit	Inspositi to	use reatures	cu conti	tings can	menuat
enstear gem	ster off of	It le. On air	le. cuitable	camera nirect	دري هو	atte camera	»*
	0	0	5	\sim	0	0	
					\checkmark		
						×	
						×	
				×	×		
	\checkmark						
	\checkmark	\checkmark	\checkmark				
	×	×	×				
	\checkmark	\checkmark	\checkmark				
	\checkmark	\checkmark					
	\checkmark						
		x	X			x	
	×	×	×				
	Image: Constraint of the sector of the se	Image: Constraint of the sector of the se	Image: select one of the select one select one select one of the select one of the select	Image: select of the select	Image: Section of the section of th	Image: Sector of the sector	Image: series of the series

1. Requires Sony CNA-1. Contact Sony for list of supported cameras.

2. Available CCU functions depend on Camera features.

3. Sony Lanc support varies between cameras. Sony, Canon and JVC have models that support generic Lanc. Some Sony models have different connectors, which require adapter cables (not available from Vinten). In general, if the camera supports 3rd party Lanc hand controllers (e.g Manfrotto) then the Vantage can control the camera. 4. Lanc support available March 2017.

5. Vinten Vantage Servo Lens Drive available April 2017.

6. On-air shot replay generally needs pan, tilt, zoom and focus recall to all be synchronised. Lenses that do not provide positional information do not allow this, and are generally unsuitable for on-air shot replay.

7. Provides access to the camera's OSD/menu and allows navigation/selection of options.