

Model Name	PTC-150T
Product Name	HD/SD-SDI PTZ Camera
Video format	1080p 59.94/50/29.97/25 Hz 1080i 59.94/50 Hz 720p 59.94/50 Hz 480i, 576i (on CVBS)
Image Sensor	1/2.8" type progressive scan CMOS sensor
Effective Pixels (approx.)	2.14 Mega pixels
Min. Illumination	Color: 0.4 lx B/W: 0.03 lx (F1.6, 1/30 sec, 50IRE, Gain: High)
Electronic Shutter	1/25 (1/30), 1/50 (1/60), 1/120 (1/100), 1/250, 1/500, 1/1000 sec
Zoom Ratio	30x Optical Zoom
Gamma Control	Off / Normal / Standard Mode 1-4
Iris Control	Auto / Manual
Digital Noise Reductions	Yes
White Balance	AWB / MWB / One push WB / Outdoor / Indoor / Fluorescent
AGC / Gain Control	Auto / Manual Max. Gain Limit
Mirror / Flip Image	Yes
Focus Mode	Auto / Manual
Panning/Tilting Range	Pan: 270°, Tilt: +90° to -20°
Panning/Tilting Speed	Manual: 1~150°/Sec Swing: 1~150°/Sec
Preset	50 Position
Field of View (Horizontal, Wide)	Approx. 63.7° (WIDE END) / 2.3° (TELE END)
Image Compensation	Day & Night function
Video Output	HDMI (V1.3) x1 HD/SD-SDI x1 CVBS x1 HDBaseT x1 to PTC-150T Receiver Box

Tally LED	Dual color (Red, Green)
Filter	Yes
Remote Control Interface and Transmit Distance	RS-422: Transmit up to 1000m HDBaseT (RJ-45)/ DVIP on Receiver Box: Transmit up to 100m
Camera Control Unit	RMC-180
Accessories	----
Color	dark blue