

# Ikan Professional 19" High Bright Teleprompter w. 19" Talent Monitor Kit (3G-SDI) (PT4900S-TMW)

## 19 in. Teleprompter

Riser Plate Height	Low: 2.06 in./52.5mm   Medium: 3.74 in./95mm   High: 5.31 in./135mm   DSLR: 6.29 in./160mm
Length of Rods	15mm x 400mm
Build Material	Chassis: Anodized Aluminum   Rods: Carbon Fiber
Reading Range	25 ft. / 7.62 m
Beamsplitter Ratio	70/30
Beamsplitter Shape	Rectangular
Beamsplitter Material	Glass
Tripod Mounts	11 x 1/4 in. -20 Female   9 x 3/8 in. -16 Female
Product Weight w/ Low Plate	22.70 lbs.
Product Weight w/ Medium Plate	23.10 lbs.
Product Weight w/ High Plate	23.23 lbs.
Product Weight w/ DSLR Plate	22.60 lbs.
Height of Teleprompter	16 in./ 406mm

# 19 in. SDI Teleprompter Monitor

Aspect Ratio	4:3
Maximum Brightness	1000 cd/m2
Screen Size (Diagonal)	18.5 in.
Mount	VESA 100mm
Video Inputs	SDI, HDMI, VGA
Input Voltage	DC 12v / 4A
Power Consumption	30W
Product Weight	6 lbs.
Product Dimensions	17 in. x 15 in. x 1 in.
Native Resolution	1280 x 1024
Viewing Angle	160° (H) / 170° (V)
Build Material	Aluminum Chassis
Image Flip	Horizontal: Yes   Vertical: Yes

# 19 in. Widescreen Talent Monitor

Aspect Ratio	16:9
Maximum Brightness	1000 cd/m2
Screen Size (Diagonal)	18.5 in.
Mount	VESA 100mm
Video Inputs	SDI, HDMI, VGA
Input Voltage	DC 12v / 5A
Power Consumption	36W
Weight of Monitor	5.73 lbs.
Product Dimensions	18.3" x 12.3 x 1.2"
Native Resolution	1920 x 1080
Viewing Angle	178° (H) / 178° (V)
Build Material	Aluminum Chassis
Image Flip	Horizontal: Yes   Vertical: Yes
Tally Interface	RJ45

## Talent Monitor Mount

Mounting System	19mm Rod, 100mm VESA
Length of Height Adjustment	1.2 in.
Weight of Mounting Bracket	1 lbs.
Dimensions of VESA Mount	6 x 9.5 x .5 in.
Dimensions of 15mm Mount	5 x 5.2 x 1 in.

**Supported Video Signal:**

SDI (Script Monitor)

720x480i @ 59.94, 60 Hz

720x576i @ 50 Hz

1280x720p @ 50, 60 Hz

1280x1024 (Native)@ 50, 59.94, 60 Hz

1920x1080i @ 50, 59.94, 60 Hz

1920x1080psf @ 24, 25, 29.97, 30 Hz

1920x1080p @ 23.93, 24, 25, 29.97, 30, 50, 59.94, 60 Hz

HDMI (Script Monitor)

720x480i & 720x480p @ 59.94, 60 Hz

720x576i & 720x576p @ 50 Hz

1280x720p @ 50, 59.94, 60 Hz

1280x1024 (Native)@ 50, 59.94, 60 Hz

1920x1080i @ 50, 59.94, 60 Hz

1920x1080psf @ 24, 25, 29.97, 30 Hz

1920x1080p @ 23.97, 24, 25, 29.94, 30, 50, 59.94, 60 Hz

SDI (Talent Monitor)

720x480i @ 59.94, 60 Hz

720x576i @ 50 Hz

1280x720p @ 50, 60 Hz

1280x1024 @ 50, 59.94, 60 Hz

1920x1080i @ 50, 59.94, 60 Hz

1920x1080psf @ 24, 25, 29.97, 30 Hz

1920x1080p (Native)@ 23.93, 24, 25, 29.97, 30, 50, 59.94, 60 Hz

HDMI (Talent Monitor)

720x480i & 720x480p @ 59.94, 60 Hz

720x576i & 720x576p @ 50 Hz

1280x720p @ 50, 59.94, 60 Hz

1280x1024 @ 50, 59.94, 60 Hz

1920x1080i @ 50, 59.94, 60 Hz

1920x1080psf @ 24, 25, 29.97, 30 Hz

1920x1080p (Native)@ 23.97, 24, 25, 29.94, 30, 50, 59.94, 60 Hz