

Compact & Travel-Friendly



SB-U50 PD

The new SB-U-PD series battery is the next generation in the popular SB-U series. It is a lithium-ion battery that is compatible with Sony BP-U Mount Cameras, such as PXW-FX9/6, FS7/FS5, and PXW/PMW-series cameras. The new SB-U-PD series improved the accuracy of battery remaining indication on the viewfinder of SONY cameras. The battery features a 14.4V D-Tap output and also USB Type-C PD input/output that can charge the battery using an optional charger. A four-LED gauge indicates the charge state of your battery. The battery's internal circuitry provides over-charge, over-discharge, and high load overcurrent protection.

Product Features

- 3.3Ah/48Wh Capacity
- Compatible with Sony PXW-FX9/6, FS7/FS5, PXW/PMW-series cameras
- Accuracy of battery remaining capacity/time indication on the viewfinder of SONY cameras and LEDs on battery
- Built-In D-Tap Output and USB-C PD (Power Delivery)
- 4-LED Power Gauge
- Charges in IDX Chargers: MC-2U, UC-PD1, UC-PD2
- Over-Charge, Over-Discharge Protection and Overcurrent Protection at High Loads

Specifications

Capacity: 48Wh 14.4V, 3.3Ah **Max Draw:** 3.2A (11V)/ 35W ‡

Power Outputs: (1) D-Tap (35W), (1) USB-C PD; Input/ Output:

30W max. (5V/3A, 9V/3A, 12V/2.5A,15V/2A)

End Voltage: 11V

Protection: Over-charge, Over-discharge, Over-current, Over-temperature

Ambient Temperature: 32~104°F (Charge), -4~113°F (Discharge), -4~122°F (Storage)

Dimensions: 1.63(w) x 2.59(H) x 2.74(D) inches

Weight: 0.6 lbs

Standard IDX two year warranty applies

Available November 2022

 $\ensuremath{^{**}\text{IDX}}$ reserves the right to change the specifications contained herein without notice







