



## Operator Control Unit OCU-1

Offering camera operators the possibility to take control of lens functions



### Operator's lens control

Focus, iris, zoom control, with additional assignable user buttons for small rigs including motorized EF lenses.

### WCU-4 override

Lets operators take control of focus, iris, and zoom at the touch of a button. Saves time while framing a shot and enables focus adjustments if necessary.

### Override screen

OCU-1 override is indicated on the WCU-4 screen and enables the focus puller to re-engage control smoothly without a jumping motor.



## Technische Daten

Connectors	2x LBUS
Supply voltage	10.5 - 34 V
Power consumption	55mA @ 24V
Operating Temperature	-20 °C to +45 °C / -4 °F to 113 °F
Size and weight without OCU-1 Rosette Bracket	44 x 65,30 mm / 1.73 x 2.57 in 165.51 g / 5.84 oz
Compatible with	<ul style="list-style-type: none"><li>- ALEXA</li><li>- AMIRA</li><li>- ALEXA Mini</li><li>- SMC-1</li><li>- EMC-1</li><li>- AMC-1</li><li>- Stabilized Remote Head SRH-3</li><li>- Sony/Red/Canon, Blackmagic (LANC) via CUB-1</li><li>- ENG Lens via CUB-2</li></ul>
Software updates devices	<ul style="list-style-type: none"><li>- WCU-4</li><li>- UMC-1</li><li>- AMC-1</li><li>- AMIRA</li><li>- ALEXA Mini</li></ul>
Special features	<ul style="list-style-type: none"><li>- Spray and dust-proof aluminum housing</li><li>- Robust mechanical and electrical interfaces</li><li>- Additional accessory available: OCU-1 Rosette Bracket</li></ul>