flowtech<sup>m</sup>100<sup>m</sup>

## The world's fastest deploying tripod now in 100mm.

sachtler 🚍

Sachtler presents the award winning flowtech. Providing an incredibly fast, lightweight and easy set up with revolutionary quick release brakes, rubber feet and a carbon fibre mid-level spreader. The award winning flowtech technology is now available in 100mm to support a payload of up to 30kg (66lb).

- Deploy and adjust your tripod in an instant: Unique quick release brakes
- Easy to transport and exceptional torsional stiffness: Ergonomic carbon fibre leg design
- Capture extremely low and high shots: Versatile hinge lock mechanism
- Fast and stable setup in narrow spaces or on uneven terrain: Unique carbon fibre mid-level spreader
- Superior performance and reliability: Extensive endurance and environmental testing

Sachtler A Vitec Group Brand



## flowtech<sup>\*</sup>100

Tripod flowtech<sup>tm</sup> 100 MS 5585

		Payload range	30kg
		Weight	2 kg - 7.01lb (tripod only)
	Ĥ	Height	
		Height range in spreaderless mode	26 - 153cm 10.2 - 60.2in
		Height range with mid-level spreader	52 - 155cm 20.5 - 61in
<b>ě</b>			

Height Weight Camera fitting Payload range					
	System FSB 10 FT MS S2045FTMS (FSB 10) S2046FTMS (FSB 10T)	System DV 12 FT MS 1205FTMS	System Video 15 FT MS 1505FTMS	System Video 18 FT MS 1811FTMS	System Cine 7+7 FT MS 1910FTMS
	4 - 12 kg 8.8 -26.5 lb	1 - 15 kg 2 - 33 lb	1 - 17 kg 2 - 37 lb	2 - 22 kg 4- 48 lb	2 - 22 kg 4- 48 lb
	Sideload S Touch & Go S	Touch & Go	Touch & Go	Touch & Go	Sideload M
	FBS10 : 6.8kg (15lb) FSB10 T: 6.9kg (15.2lb)	7.3kg / 16.1lb	7. 4kg / 16.3lb	8.2kg / 18.1lb	8.3 kg / 18.3lb
Height range in spreaderless mode	41 - 170cm 16.1 - 66.9in	41 - 170cm 16.1 - 66.9in	41 - 170cm 16.1 - 66.9in	42 - 172cm 16.5 - 67.7in	41 - 170cm 16.1 - 66.9in
Height range with mid-level spreader	71 - 172cm 28 - 67.7in	71 - 172cm 28 - 67.7in	71 - 172cm 28 - 67.7in	72 - 173cm 28.3 - 68.1in	71 - 172cm 28 - 67.7in

## **NEW** carbon fibre mid-level spreader

For a fast and stable setup in narrow spaces or on uneven terrain. Four locking positions for simple setup and fast repositioning.

Weight: 660g (1.45lb) Built-up radius: 29-41.5cm (11.4-16.3in)

