

sachtler 

Videndum

aktivTM
sachtler.com/aktiv





aktivTM

Videndum






Level up with aktiv™

the fluid head built for speed.

When you have just one chance to capture the perfect shot, mount, level and lock the revolutionary aktiv™ fluid head in seconds.

Sachtler's unique SpeedLevel™ and SpeedSwap™ technologies deliver the fastest way to place and position your camera; adjust the level in an instant without ever taking your eye off the action; get closer to the ground than ever before for extreme low-angle shots or swap between a tripod, slider, or hand held without missing a beat. Capture the widest range of shots in the shortest time with aktiv™.






Ambassadors

Geoff Nelson

The speed of set up of the flowtech and aktiv system is beyond anything that I've ever used. The flowtech tripod is ready in seconds.

The aktiv series and flowtech combination really has no competitor. It allows you to work with a lightweight system that is easy to use, efficient and fast. My experience so far has been phenomenal.




Andreas Niederkofler

With the aktiv18T, I can perfectly balance my heavier rig in seconds. The whole system is so compact it's easy to carry between locations. Compared to my previous setup, I'm faster on every shot – and that speed often means I capture moments that would otherwise be gone.

Level up and lock your head in an instant.

Never miss the shot. aktiv™ fluid heads feature revolutionary SpeedLevel™ technology. Release, level, and lock your head tightly into the perfect position without missing a second of action.



Unique SpeedLevel™ technology.





Capture extreme low-angle shots right down to the ground.

Go lower than ever. aktiv™ and flowtech® combine to provide a flexible one tripod solution delivering the widest height range. With no bowl clamp required, aktiv™ heads allow flowtech® tripods to go flat to the ground for the perfect low-angle shot.



Innovative streamlined mounting system.



Switch between tripod and slider in seconds.

Stay fast for ultimate creativity. aktiv™ fluid heads feature the unique SpeedSwap™ system, allowing lightning-fast camera swaps from a tripod to a slider without missing a beat. The perfect camera movement is just a SpeedSwap™ away.



Revolutionary SpeedSwap™ system.



Visible from any height or angle - day or night.

Clear confirmation that the camera is level comes from the illuminated PrismBubble visible from any height or angle – day or night.



Innovative PrismBubble.



Head Overview | 75 mm



aktiv™6
S2064S



aktiv™8
S2068S



aktiv™8T
S2068T

Bowl	75 mm with SpeedSwap™	75 mm with SpeedSwap™ base	75 mm with SpeedSwap™ base
Payload range	0 - 8 kg / 0 - 17.6 lb	0 - 12 kg / 0 - 26.5 lb	0 - 12 kg / 0 - 26.5 lb
Counterbalance steps	15+0	15+0	15+0
Drag setting	3+0	7+0	7+0
Head Weight	2.6 kg / 5.7 lb	2.7 kg / 5.9 lb	2.8 kg / 6.2 lb
Camera fitting	Sideload S	Sideload S	Touch & Go plate S
Sliding range	120 mm / 4.7 in	120 mm / 4.7 in	60 mm / 2.4 in
Tilt range	+90° to -70°	+90° to -70°	+90° to -70°
Temperature range	-40°C to +60°C / -40°F to +140°F	-40°C to +60°C / -40°F to +140°F	-40°C to +60°C / -40°F to +140°F

Head Overview | 100mm



aktiv™10
S2072S



aktiv™10T
S2072T



aktiv™16T
S2086T



aktiv™18T
S2088T

Bowl	100 mm with SpeedSwap™ base	100 mm with SpeedSwap™ base	100 mm with SpeedSwap™ base	100 mm with SpeedSwap™ base
Payload range	0 - 12 kg / 0 - 26.5 lb	0 - 12 kg / 0 - 26.5 lb	0 - 16 kg / 0 - 35.3 lb	0-18 kg / 0-39.7 lb
Counterbalance steps	15+0	15+0	15+0	15+0
Drag setting	7+0	7+0	7+0	7+0
Head Weight	2.9 kg / 6.4 lb	3 kg / 6.6 lb	3.4 kg / 7.5 lb	3.4 kg / 7.5 lb
Camera fitting	Sideload S	Touch & Go S	Touch & Go 16	Touch & Go 16
Sliding range	120 mm / 4.7 in	60 mm / 2.4 in	70 mm / 2.8 in	70 mm / 2.8 in
Tilt range	+90° to -70°	+90° to -70°	+90° to -70°	+90° to -70°
Temperature range	-40°C to +60°C / -40°F to +140°F	-40°C to +60°C / -40°F to +140°F	-40°C to +60°C / -40°F to +140°F	-40°C to +60°C / -40°F to +140°F

System Overview | Mid-level spreader | 75 mm



**System aktiv™6
flowtech75 MS
S2064S-FTMS**



**System aktiv™8
flowtech75 MS
S2068S-FTMS**



**System aktiv™8T
flowtech75 MS
S2068T-FTMS**

Bowl	75 mm with SpeedSwap™ base	75 mm with SpeedSwap™ base	75 mm with SpeedSwap™ base
Payload range	0 - 8 kg / 0 - 17.6 lb	0 - 12 kg / 0 - 26.5 lb	0 - 12 kg / 0 - 26.5 lb
Counterbalance steps	15+0	15+0	15+0
Drag setting	3+0	7+0	7+0
System Weight	6.2 kg / 13.7 lb	6.3 kg / 13.9 lb	6.4 kg / 14.1 lb
Camera fitting	Sideload S	Sideload S	Touch & Go S
Sliding range	120 mm / 4.7 in	120 mm / 4.7 in	60 mm / 2.4 in
Tilt range	+90° to -70°	+90° to -70°	+90° to -70°
Temperature range	-40°C to +60°C / -40°F to +140°F	-40°C to +60°C / -40°F to +140°F	-40°C to +60°C / -40°F to +140°F
Height range with spreader	79 - 174 cm / 31 - 68.5 in	79 - 174 cm / 31.1 - 68.5 in	79 - 174 cm / 31.1 - 68.5 in
Height range without spreader	23 - 170 cm / 9.0 - 66.9 in	23 - 170 cm / 9.0 - 66.9 in	23 - 170 cm / 9.0 - 66.9 in
Transport length	85 cm / 33.5 in	85 cm / 33.5 in	85 cm / 33.5 in
Tripod stages	2	2	2
Tripod material	Carbon fibre	Carbon fibre	Carbon fibre

System Overview | Grounder spreader | 75 mm



**System aktiv™6
flowtech75 GS
S2064S-FTGS**



**System aktiv™8
flowtech75 GS
S2068S-FTGS**



**System aktiv™8T
flowtech75 GS
S2068T-FTGS**

Bowl	75 mm with SpeedSwap™ base	75 mm with SpeedSwap™ base	75 mm with SpeedSwap™ base
Payload range	0 - 8 kg / 0 - 17.6 lb	0 - 12 kg / 0 - 26.5 lb	0 - 12 kg / 0 - 26.5 lb
Counterbalance steps	15+0	15+0	15+0
Drag setting	3+0	7+0	7+0
System Weight	6.4 kg / 14.1 lb	6.5 kg / 14.3 lb	6.6 kg / 14.5 lb
Camera fitting	Sideload S	Sideload S	Sideload S
Sliding range	120 mm / 4.7 in	120 mm / 4.7 in	60 mm / 2.4 in
Tilt range	+90° to -70°	+90° to -70°	+90° to -70°
Temperature range	-40°C to +60°C / -40°F to +140°F	-40°C to +60°C / -40°F to +140°F	-40°C to +60°C / -40°F to +140°F
Height range with spreader	56 - 176 cm / 22 - 69.3 in	79 - 174 cm / 31.1 - 68.5 in	79 - 174 cm / 31.1 - 68.5 in
Height range without spreader	23 - 170 cm / 9.0 - 66.9 in	56 - 176 cm / 22.0 - 69.3 in	56 - 176 cm / 22.0 - 69.3 in
Transport length	85 cm / 33.5 in	85 cm / 33.5 in	85 cm / 33.5 in
Tripod stages	2	2	2
Tripod material	Carbon fibre	Carbon fibre	Carbon fibre

System Overview | Mid-level spreader | 100 mm



**System aktiv™10
flowtech100 MS
S2072S-FTMS**



**System aktiv™10T
flowtech100 MS
S2072T-FTMS**



**System aktiv™16T
flowtech100 MS
S2086T-FTMS**



**System aktiv™18T
flowtech100 MS
S2088T-FTMS**

Bowl	100 mm with SpeedSwap™	100 mm with SpeedSwap™	100 mm with SpeedSwap™	100 mm with SpeedSwap™
Payload range	0 - 12 kg / 0 - 26.5 lb	0 - 12 kg / 0 - 26.5 lb	0 - 16 kg / 0 - 35.3 lb	0-18 kg / 0-39.7 lb
Counterbalance steps	15+0	15+0	15+0	15+0
Drag setting	7+0	7+0	7+0	7+0
System Weight	6.9 kg / 15.2 lb	7 kg / 15.3 lb	7.5 kg / 16.5 lb	7.5 kg / 16.5 lb
Camera fitting	Sideload S	Touch & Go S	Touch & Go 16	Touch & Go 16
Sliding range	120 mm / 4.7 in	60 mm / 2.4 in	70 mm / 2.8 in	70 mm / 2.8 in
Tilt range	+90° to -70°	+90° to -70°	+90° to -70°	+90° to -70°
Temperature range	-40°C to +60°C / -40°F to +140°F	-40°C to +60°C / -40°F to +140°F	-40°C to +60°C / -40°F to +140°F	-40°C to +60°C / -40°F to +140°F
Height range with spreader	71 - 172 cm / 27.9 - 67.7 in	71 - 172 cm / 27.9 - 67.7 in	71 - 172 cm / 27.9 - 67.7 in	71 - 172 cm / 27.9 - 67.7 in
Height range without spreader	23 - 170 cm / 9.0 - 66.9 in	23 - 170 cm / 9.0 - 66.9 in	23 - 170 cm / 9.0 - 66.9 in	23 - 170 cm / 9.0 - 66.9 in
Transport length	87 cm / 34.3 in	87 cm / 34.3 in	87 cm / 34.3 in	87 cm / 34.3 in
Tripod stages	2	2	2	2
Tripod material	Carbon fibre	Carbon fibre	Carbon fibre	Carbon fibre

System Overview | Grounder spreader | 100 mm



**System aktiv™10
flowtech100 GS
S2072S-FTGS**



**System aktiv™10T
flowtech100 GS
S2072T-FTGS**



**System aktiv™16T
flowtech100 GS
S2086T-FTGS**



**System aktiv™18T
flowtech100 GS
S2088T-FTGS**

Bowl	100 mm with SpeedSwap™	100 mm with SpeedSwap™	100 mm with SpeedSwap™	100 mm with SpeedSwap™
Payload range	0 - 12 kg / 0 - 26.5 lb	0 - 12 kg / 0 - 26.5 lb	0 - 16 kg / 0 - 35.3 lb	0 - 18 kg / 0 - 39.7 lb
Counterbalance steps	15+0	15+0	15+0	15+0
Drag setting	7+0	7+0	7+0	7+0
System Weight	6.8 kg / 15 lb	7 kg / 15.3 lb	7.4 kg / 16.3 lb	7.4 kg / 16.3 lb
Camera fitting	Sideload S	Touch & Go S	Touch & Go 16	Touch & Go 16
Sliding range	120 mm / 4.7 in	60 mm / 2.4 in	70 mm / 2.8 in	70 mm / 2.8 in
Tilt range	+90° to -70°	+90° to -70°	+90° to -70°	+90° to -70°
Temperature range	-40°C to +60°C / -40°F to +140°F	-40°C to +60°C / -40°F to +140°F	-40°C to +60°C / -40°F to +140°F	-40°C to +60°C / -40°F to +140°F
Height range with spreader	60 - 176 cm / 23.6 - 69.3 in	60 - 176 cm / 23.6 - 69.3 in	60 - 176 cm / 23.6 - 69.3 in	60 - 176 cm / 23.6 - 69.3 in
Height range without spreader	23 - 170 cm / 9.0 - 66.9 in	23 - 170 cm / 9.0 - 66.9 in	23 - 170 cm / 9.0 - 66.9 in	23 - 170 cm / 9.0 - 66.9 in
Transport length	87 cm / 34.3 in	87 cm / 34.3 in	87 cm / 34.3 in	87 cm / 34.3 in
Tripod stages	2	2	2	2
Tripod material	Carbon fibre	Carbon fibre	Carbon fibre	Carbon fibre

SpeedSwap™ Accessories

Switch between tripod and slider in seconds with the revolutionary SpeedSwap™ system. Stay fast for ultimate creativity. All aktiv fluid heads feature the unique SpeedSwap system, allowing lightning-fast camera swaps from a tripod to a slider without missing a beat. The perfect camera movement is just a SpeedSwap away.



sachtler 



**Adaptor aktiv™
head / slider 75 mm**
S2080-0003



**Adaptor aktiv™
slider / tripod 75 mm**
S2080-0005



**Adaptor
aktiv head / slider 100 mm**
S2080-0004



**Adaptor
aktiv slider / tripod 100 mm**
S2080-0006

