


System	NH30 (Head) + QL40B (Tripod) + BR-2B (Mid-level spreader) + FP-1B (Large rubber feet) + RC-40 (Carrying case)		
Payload	10 kg / 22.0 lb	Tilt angle	+90° / -70°
Weight	4.9 kg / 10.8 lb	Pan angle	360°
Height	① H : 1975 mm W : 780 mm (※Reference)	Counterbalance	Range : 0 ~ 10 kg / 0 ~ 22 lb (C.G. 55 mm)
	② H : 910 mm W : 550 mm (")		System: free plus 5 steps
Folded length	③ L : 944 mm (")	Drag mode	Free plus 3 steps
Camera plate (Sliding range)	2 Sliding plates (compatible with Manfrotto and Sachtler)	Drag system	Multilayered Metal Structure
	One touch attach and release mechanism	Temperature range	-40°C ~ +60°C / -40°F ~ +140°F
Plate attachment (Screw sliding range)	Standard : ±30 mm / ±1.2" , Long : ±85 mm / ±3.3"	Head base	Ball 75 mm / Flat base with 3/8" female thread
	Standard : 1/4-20UNC (with video boss)	Carrying handle	Included
Spare screw	Long : 1/4-20UNC × 1 , 3/8-16UNC × 2	Section	2-Stage
	Standard : 68 mm / 2.6" , Long : 85 mm / 3.3"	Leg lock system	Flip lock
Accessory port	1/4-20UNC × 1 , 3/8-16UNC × 1	Spreader	BR-2B (Telescopic , Removable)
	Equipped on the top of the head (beneath sliding plate)	Pan handle	Dedicated pan handle
		Case material	Nylon , Polyester , TPE , PE , PP , POM

Remarks

* Includes adjustment tool.

■Exterior Dimensions (mm)



※ Reference

