

# 4K Rack/Field Monitor SDI, HDMI2.0, DVI, VGA





Model: RM3G-4K

#### **Display**

15.6" IPS 4K 3840x2160 Aspect Ratio 16:9 Contrast 1000:1 Viewing Angle 176°

### **Power**

Input Voltage 12 - 24VDC (XLR), 15W max

#### **Physical**

Dimensions 6U 482.5 x 267.0 x 38.0mm Weight 3.4kg / 12kg with Case

#### **Included**

Monitor mounted inside 19" Carrying Case Power Adapter, Tally Connector Folding Sun Shade, V-Mount Battery Plate Anton Bauer Optional

#### **Environment**

Operating Temperature 0C to 40C Non-Operating Temperature -20C to 60C

#### Warranty

2 Years

# **Video Inputs**

1x 3GA-SDI 1x HDMI2.0 (4k60) 3x HDMI1.4 (4k30)

1x DVI

1x VGA

1x Tally

## **Video Outputs (Loopouts)**

1x 3GA-SDI

#### **Audio**

1x Unbalanced Stereo Input

1x Audio Speaker

1x Audio Headphones (Front)

## **Front Panel Controls**

Video Input Selection, Display Adjustments, Tally indicator lights, Center and Safety Markers, Aspect Ratio, System Settings, H/V Delay, Check Field, Underscan, Signal Loss Color Bars, Zoom, Image Flip, PIP

#### Quad View / PIP

All inputs can be used in any combination.

