



PL-E60P 60W 1:1

DMX

IP54

21mm

thin



PL-E90P 90W 2:1

DMX





Edge SMD-LEDs

Mount SMD-LEDs on the side of the light, to make the light only 21mm thickness with diffuser.

The innovative bottom reflection glass has laser dots with calculated spaces, so that the multi angles of edge light will be converged on the laser dots, and output 90° to the front with minimum light lost.

Edge Mounted SMD LEDs



Edge Mounted SMD LEDs

Reflection glass with calculated laser dots



IP54 Weather Proof

| Model | Test Item | Test Result | Report No. |
|---------|------------------------------|-------------|-------------|
| PL-E60P | Degrees of protection | PASS | WT193600427 |
| PL-E90P | provided by enclosure (IP54) | PASS | WT193600428 |

Recommended IP54 batteries:



PB-R160S+

160Wh 200W/16A load 1.5m drop proof IP54 proof



PB-R290S+

290Wh 250W/20A load 1.5m drop proof IP54 proof



Accessories and Package



Optional barn door LA-HE60: for PL-E60P LA-HE90: for PL-E90P



Optional 40° Honeycomb LA-GE60: for PL-E60P LA-GE90: for PL-E90P



Provide 3-light Kit with Trolley case, Including Light Stands and Power adaptors



Specifications

| Model | PL-E60P | PL-E90P |
|-----------------|-----------------|-----------------|
| Input votage | DC 11-36V | DC 11-36V |
| Power | 60W | 90W |
| Illuminance | 1500Lux @ 1m | 2200Lux @ 1m |
| Color Temp | 2700K-6500K | 2700K-6500K |
| Color rendering | CRI 98; TLCI 99 | CRI 98; TLCI 99 |
| IP class | IP54 | IP54 |
| DMX | DMX512 in&out | DMX512 in&out |

SWIT Electronics Co., Ltd. +86-25-85805753 http://www.swit.cc Email: contact@swit.cc SWIT Electronics America, Inc 1-(408)260-8258 http://www.switusa.com Email: info@swit.us **SWIT Electronics Europe GmbH** +49(0)20659799339 http://www.switeu.com Email: info@swit-europe.com





Facebook Page