

System	H15 (Head) + QL40B (Tripod) + SP-1B (Floor spreader) + RC-40 (Carrying case)		
Payload	3 kg / 6.6 lb	Tilt angle	+90° / -70°
Weight	6.1 kg / 13.5 lb	Pan angle	360°
Height	① H : 1983 mm W : 710 mm (※Reference)	Counterbalance	Range : 0.8 ~ 2 kg / 1.7 ~ 4.4 lb (C.G. 55 mm)
	② H : 715 mm W : 1090 mm (")		Perfect Balance
Folded length	③ L : 944 mm (")	Continuous Counterbalance with Illuminated Meter	
Camera plate (Sliding range)	Sliding plate (compatible with Manfrotto and Sachtler)	Drag mode	Free plus 3 steps
	One touch attach and release mechanism	Drag system	Multilayered Metal Structure
Plate attachment (Screw sliding range)	±30 mm / ±1.2"	Temperature range	-40°C ~ +60°C / -40°F ~ +140°F
Spare screw	1/4-20UNC (with video boss)	Head base	Ball 75 mm / Flat base with 3/8" female thread
	68 mm / 2.6"	Carrying handle	Included
Bubble level	1/4-20UNC × 1 , 3/8-16UNC × 1	Section	2-Stage
	Equipped on the top of the head (beneath sliding plate)	Leg lock system	Flip lock
Accessory port	1/4" and 3/8" screw holes (head : 1 set , tripod : 3 sets)	Spreader	SP-1B (Telescopic , Removable)
		Pan handle	PH-6B (Telescopic)
		Case material	Nylon , Polyester , TPE , PE , PP , POM

Remarks

* Includes adjustment tool.

■ Exterior Dimensions (mm)

