

Name Parameter	Solidcom C1 No Hub Version	Solidcom C1 With Hub	Mars T1000	Syscom 1000T	Solidcom M1
Transmission Range	1000ft	1000ft	1000ft	1000ft	1300ft (Build-in Antenna) 985ft (External FRP Antenna)
Picture		নির্দ্ধিত্ব			
Full-Duplex	Yes	Yes	Yes	Yes	Yes
Tally	No	No	Yes	Yes	No
Group Function	No	Two groups (W/ HUB)	No	No	Yes Max 3 Groups
2W	No	Yes, XLR(IN/OUT)	No	No	Yes, XLR(IN/OUT)
4w	No	Yes, RJ45(IN/OUT)	Yes, RJ45(IN/OUT)		Yes, RJ45(IN/OUT)
Cascade	No	No-limit(cascade with 4W; or IP digital signal)	Yes, Max 2 Sets, 10 Users to talk;	Yes, Max 2 Sets	No-limit
Antenna	Bulit-In	External Antenna	High-Gain Basestation Antenna	Panel Antenna (Self-Buying)	Built-in High Gain Ant OR (External FRP Antenna)
Frequency Band	1.9GHz *	1.9GHz *	1.9GHz *	1.9GHz *	1.9GHz *
Power	Headset battery: Removable lithium battery (each headset comes stardard with 2 batteries)	Headset battery: Removable lithium battery (each headset comes stardard with 2 batteries)	Basestation DC Input NP-F Type Battery	Basestation DC Input AC Input	Basestation POE Power Supply NP-F Type Battery
	HUB: Supports NP-F battery, V-Mount battery, 12VDC adapter	HUB: Supports NP-F battery, V-Mount battery, 12VDC adapter	Beltpack 1600mAh Lithium Polymer Battery	Beltpack 1600mAh Lithium Polymer Battery	Beltpack 1500mAh Lithium Polymer Battery
Beltpack Qty	2-person headsets up to 6-person headsets	8S: 9-person system(The hub supports talk function)	1 Basestation 4 Beltpacks	1Basestation 4 Beltpacks OR 8 Beltpacks;	1Basestation 4 Beltpacks OR 8 Beltpacks;
Communications Standard	DECT 6.0	DECT 6.0	DECT 5.0	DECT 5.0	DECT 6.0
	*:The frequency bands of different countries or regions may be different, please consult Hollyland for specific information;				

 $[\]star \vdots \\ \text{The frequency bands of different countries or regions may be different, please consult Hollyland for specific information;}$